DELTA-THERM.COM

DELTA-THERM

FLOOR WARMING QUOTE REQUEST FORM

Date: _____

Customer Name: _____

Phone: _____

Fax: _____

Project Name: _____

Type of Area to be Heated: _____

Project Location: _____

Project Phase: _____

Quote Due By: _____

1. What voltages are available?
   - ☐ 120
   - ☐ 208
   - ☐ 240
   - ☐ 277

2. What is the sq. footage of the open area to be heated?

   You cannot heat under built-in fixtures and cable cannot be installed in walls. The open area to be heated = total room area - built-in fixture areas.

   _____

3. Will the floor contain expansion joints?
   - ☐ Yes
   - ☐ No

4. Will the floor warming system be used for primary heat in addition to floor warming?
   - ☐ Yes, Please Specify the Room Heat Loss: _____
   - ☐ No

5. What type of embedding material will you be using?
   - ☐ Thin Set
   - ☐ Self-Leveling Compound
   - ☐ Concrete
   - ☐ Other, Please Specify: _____

6. How thick will the embedding layer be? _____

7. What type of floor covering will be installed over the floor warming system (R-Value needs to be below 2.5)?
   - ☐ Tile, Marble, or Stone
   - ☐ Laminate or Floating Hardwood
   - ☐ Hardwood with Sleepers
   - ☐ Vinyl
   - ☐ Carpet and Padding
   - ☐ Other, Please Specify: _____

8. Would you like us to quote 2FW cable, FW cable, M.I. cable or Radiance Mats?
   - ☐ 2FW Cable
   - ☐ FW Cable
   - ☐ FE Radiance Mats
   - ☐ M.I. Single Conductor Floor Warming Cable Assembly
   - ☐ Please Recommend

9. What is the distance to the nearest junction box or control? _____

10. What type of control would you like us to quote?
    - ☐ F15A (120/208/240 VAC thermostat)
    - ☐ Other, 277VAC application

11. Will you need a panel?
    - ☐ Low Noise Relay Panel
    - ☐ Enclosed Contactor Panel
    - ☐ Custom Control/Monitor Panel
    - ☐ Please Recommend
    - ☐ Do Not Need A Panel

Comments:

_____

_____

_____

Please fax this form to: (847) 526-4456
On-line form can be submitted on www.delta-therm.com

PLEASE FAX OR E-MAIL INFO@DELTA-THERM.COM
A DRAWING OF THE ROOM(S) WITH BUILT-IN FIXTURES