



- A. 1 - Fiberglass Box (6" x 4" x 3") - includes CID2 LED with pre-terminated lead wires (14AWG)
B. 1 - 3/4" Hub
C. 1 - Lock nut

The ML-360 is an end-of-line device, not to be used to attach power to heating cable.

Order Delta-Therm Power Connection Kits separately:

PCK-HLC	IN or HT Series in Hazardous locations
PCK-PT/PF	Constant Wattage (CW) Series
PCK-HT	High Temperature HT Series
PCK-IN	Industrial (IN) Series
PCK-C6	Commercial (CO) Series
PCK-TT	Thrifty Trace Series

Installation

Using the appropriate Power Connection Kit, simply connect to the 14 AWG lead wires as you would for incoming power.

If the kit contains a connector, thread the connector into the hub.

ML-360

LED Monitor Light (CID2 Hazardous and Ordinary Locations)

DESCRIPTION

The Delta-Therm ML-360 Monitor Light allows quick 360° visibility of electrical power being applied. The monitor light is on when the cable is on.

The ML-360 Monitor Light is **component only**. Easy to install, the device is designed for use with an appropriate power connection kit.

ML-360 FEATURES

- Viewable 360°
- NEMA 4X rated box
- Monitor Light operates from 20 to 277VAC
- CID2 Rated LED Light
- Pre-terminated 14AWG lead wires
- Simple installation



TECHNICAL SUPPORT

Please call 1-800-526-7887 with any questions.