

## **PPS-GS-75**

## **PPS-SS-75**

### **Pre-Punched Galvanized and Stainless Steel Strapping**



#### **DESCRIPTION**

The PPS-GS-75 or PPS-SS-75 pre-punched strapping is used to anchor M.I. snow melting cable assemblies at a consistent spacing to the base asphalt pour.

The pre-punched tabs are spaced 1" (2.5cm) apart.

PPS-GS-75 Pre-punched galvanized strapping, 75' roll.  
(stock)

PPS-SS-75 Pre-punched stainless steel strapping, 75' roll.  
(non-stock)

Please call Delta-Therm at 1-800-526-7887 if you have any questions.

## INSTALLING

Lay two parallel rows of strapping on top of the 1.5" (4cm) base layer of asphalt.

Using 3" - 4" (8cm - 10cm) long nails, secure the strapping on top of the base layer of asphalt.

The strapping tabs are spaced 1" (2.5cm) apart. Using the tabs, secure the M.I. snow melting cable assembly to the strapping at the specified cable spacing. Refer to Detail 1.

Please call Delta-Therm at 1-800-526-7887 if you have any questions.



**Detail 1.** Attaching MI cable to strapping.

## TECHNICAL SUPPORT

A full set of installation instructions is included with order.  
Please call 1-800-526-7887 with any questions.