



# DT-BAH Series

## Medium Wave Comfort



DT-BAH-35A-17 shown



MODEL NO.	VOLTS	kW	WATTS	AMP	BTU/h	LENGTH	WIDTH	HEIGHT	SHIP WEIGHT
DT-BAH-18-A-05	120	0.5	500	4.2	1,700	18" (457 mm)	6.75" (172 mm)	6.4" (163 mm)	8 lbs (3.6 kg)
DT-BAH-25-A-10	120	1.0	1,000	8.3	3,400	25" (635 mm)	6.75" (172 mm)	6.4" (163 mm)	10 lbs (4.5 kg)
DT-BAH-25-B-10	208	1.0	1,000	4.8	3,400	25" (635 mm)	6.75" (172 mm)	6.4" (163 mm)	10 lbs (4.5 kg)
DT-BAH-25-C-10	240	1.0	1,000	4.2	3,400	25" (635 mm)	6.75" (172 mm)	6.4" (163 mm)	10 lbs (4.5 kg)
DT-BAH-35-A-17 <sup>2</sup>	120	1.7	1,750	14.0	5,900	35" (889 mm)	6.75" (172 mm)	6.4" (163 mm)	13 lbs (5.9 kg)
DT-BAH-35-B-17 <sup>2</sup>	208	1.7	1,750	8.3	5,900	35" (889 mm)	6.75" (172 mm)	6.4" (163 mm)	13 lbs (5.9 kg)
DT-BAH-35-C-17 <sup>2</sup>	240	1.7	1,750	7.0	5,900	35" (889 mm)	6.75" (172 mm)	6.4" (163 mm)	13 lbs (5.9 kg)
DT-BAH-45-B-25 <sup>2</sup>	208	2.5	2,500	12.0	8,500	45" (1143 mm)	6.75" (172 mm)	6.4" (163 mm)	16 lbs (7.3 kg)
DT-BAH-45-C-25 <sup>2</sup>	240	2.5	2,500	10.0	8,500	45" (1143 mm)	6.75" (172 mm)	6.4" (163 mm)	16 lbs (7.3 kg)
DT-BAH-60-B-30 <sup>1,2</sup>	208	3.0	3,000	14.0	10,200	60" (1524 mm)	6.75" (172 mm)	6.4" (163 mm)	20 lbs (9.1 kg)
DT-BAH-60-C-30 <sup>1,2</sup>	240	3.0	3,000	12.0	10,200	60" (1524 mm)	6.75" (172 mm)	6.4" (163 mm)	20 lbs (9.1 kg)
DT-BAH-60-C-40 <sup>1,2</sup>	240	4.0	4,000	16.5	13,500	60" (1524 mm)	6.75" (172 mm)	6.4" (163 mm)	20 lbs (9.1 kg)

DT-BAH Series heaters are NOT for home or recreational use. DO NOT USE in the home, mobile home, RV's, tents, etc.

<sup>1</sup>Not available to ship via UPS. Truckline only.

<sup>2</sup>Heater is stocked and will ship from Detroit Radiant Products Company. Non-stocked heaters may ship from Brantford, Ontario. Subject to 6-8 week lead time.

### BAH SERIES REPLACEMENT LAMP ELEMENTS

LAMP PART NO.	VOLTS	WATTS /LAMP	FOR USE WITH	LAMP LENGTH	SHIP WEIGHT
DT-QT-18-A-05	120	500	BAH-18-A-05	18" (457 mm)	5 lbs (2.3 kg)
DT-QT-25-A-10	120	1,000	BAH-25-A-10	25" (635 mm)	5 lbs (2.3 kg)
DT-QT-25-B-10	208	1,000	BAH-25-B-10	25" (635 mm)	5 lbs (2.3 kg)
DT-QT-25-C-10	240	1,000	BAH-25-C-10	25" (635 mm)	5 lbs (2.3 kg)
DT-QT-35-A-17	120	1,750	BAH-35-A-17	35" (889 mm)	5 lbs (2.3 kg)
DT-QT-35-B-17	208	1,750	BAH-35-B-17	35" (889 mm)	5 lbs (2.3 kg)
DT-QT-35-C-17	240	1,750	BAH-35-C-17	35" (889 mm)	5 lbs (2.3 kg)
DT-QT-45-B-25	208	2,500	BAH-45-B-25	45" (1143 mm)	7 lbs (3.2 kg)
DT-QT-45-C-25	240	2,500	BAH-45-C-25	45" (1143 mm)	7 lbs (3.2 kg)
DT-QT-60-B-30	208	3,000	BAH-60-B-30	60" (1524 mm)	7 lbs (3.2 kg)
DT-QT-60-C-30	240	3,000	BAH-60-C-30	60" (1524 mm)	7 lbs (3.2 kg)
DT-QT-60-C-40	240	4,000	BAH-60-C-40	60" (1524 mm)	7 lbs (3.2 kg)
DT-QT-60-D-40	575	4,000	BAH-60-D-40	60" (1524 mm)	7 lbs (3.2 kg)

### LIMITED WARRANTY GUIDELINES AND OPTIONS

All limited warranties, are defined in the product insert manual for the particular series of heaters.

Please contact the factory for further information on the terms and conditions.

Heater Components	Replacement Elements
1 YEAR	1 YEAR

The use of a contactor panel may be required when 24V control is desired or when total amperage exceeds control device limitations. See Delta-Therm Load Switching Panels at [www.delta-therm.com](http://www.delta-therm.com) for more information.

Manufactured for Delta-Therm by Detroit Radiant Products Company in Warren, MI.