

## SNOW SWITCH MODEL APS-3C

### Automatic snow/ice melting system control panel

The APS-3C Snow Switch when used with compatible sensors automatically controls snow/ice melting heaters, ensuring minimum operating costs. Typical applications include pavement, sidewalk, loading dock, roof, gutter and down spout snow/ice melting. The APS-3C is interchangeable with earlier APS-3 models.

The adjustable hold-on timer continues heater operation for up to 10 hours after snow stops to ensure complete melting. The optional RCU-3 Remote Control Unit can be located where system operation can be conveniently observed. It duplicates many of the controls and indicators on the APS-3C front panel. It is used to clear tracked and drifting snow that may not land on a sensor.

The calibrated 40°F to 90°F (4°C to 32°C) high limit thermostat prevents excessive temperatures when using constant wattage and MI heaters. It also permits safe testing at outdoor temperatures too high for continuous heater operation. The temperature sensor is included.

The APS-3C provides a relay closure interface for use with energy management computers (EMC). This feature can also be used for general purpose remote control and annunciation and other advanced applications.

All sensor and communications wiring is NEC Class 2. This simplifies installation while enhancing fire and shock safety. The APS-3C can interface up to six sensors from the CIT-1 product family. Using more sensors provides superior performance by better matching the controller to site performance requirements.

The APS-3C is an exceptionally capable deicing controller. For complete information describing its application, installation and features, please contact Customer Service or check on the web at [www.networketi.com](http://www.networketi.com).



### Features and Benefits

- Automatic snow/ice melting control
- Operates electrically- and mechanically- held contactors for pilot duty applications
- Energy management computer (EMC) interface
- Accommodates MI, constant wattage and self-limiting heaters
- Multiple sensor capability
- Heater hold-on and test capabilities • C-UL-US
- Simple to install and operate
- Low system costs
- Minimum energy costs

## Specifications

### General

Area of use:	Non-hazardous locations
Approvals:	C-UL-US Type 873 Temperature Regulating Equipment Also evaluated by Underwriters Laboratories Inc® in accordance with UL 1053 Ground-Fault Sensing and Relaying Equipment

### Enclosure

Protection:	NEMA 3R
Cover attachment:	Hinged polycarbonate cover, lockable
Entries:	One 1-1/16" entry (top) for NEC Class 2 connections Two 1-1/16" entries (bottom) for supply and load power, except 277V single phase Two 1-1/16" entries (bottom) for supply and load power, 277 V single phase only
Material:	Polycarbonate
Mounting:	Wall mount
Dimensions:	9 .125" (L) x 11.500" (W) x 6.56 2" (H) 232mm (L) x 292mm (W) x 167mm (H)

### Control

Supply voltage:	120 VAC, 50/60 Hz, 35 VA 208-240 VAC, 50/60 Hz, 35 VA
Load:	120 VAC, 24 amp max. inductive 240 VAC, 24 amp max. inductive
Contact type:	3 Form C
Weight:	3 Pounds
Maximum ratings:	Voltage: 240 VAC Current: 24 amps
Heater hold-on timer:	0 to 10 hours; actuated by snow stopping or toggle switch
System test:	Switch toggles heater contact on and off. If temperature exceeds optional high limit thermistor (45°F), heater shuts off to reduce costs and prevent damage.

### Front panel interface

Status indicator:	- SUPPLY (green): Power on - HEAT (yellow): Heating cycle in progress - SNOW (yellow): Sensor(s) detect snow
-------------------	--

### Communication Bus

Number of cascaded units:	Unlimited
Contact delay:	5 second
Bus-wire type:	3-wire jacketed cable
Circuit type:	NEC Class 2
Lead length:	Up to 500' (152m) using 18 AWG 2-wire jacketed cable Up to 1,000' (304m) using 12 AWG 2-wire jacketed cable

### Ground Fault Equipment Protection (GFEP)

The APS-3C Snow Switch does not come with built-in GFEP protection even though a GFEP LED light is present on the controller. This is due to sharing the same circuit board as an APS-4C Snow Switch. If GFEP is needed then consider using an APS-4C Snow Switch Controller.

### Environmental


Operating temperature:	-40°F to 160°F (-40°C to 71°C)
Storage temperature:	-50°F to 180°F (-45°C to 82°C)

## Ordering Information

Order Number	Description
22470	APS-3C Control Panel, 120 VAC
22471	APS-3C Control Panel, 208-240 VAC

Accessories	Description
21357	RCU-3 Remote Control (Optional)
25076	Temperature Sensor w/ 20' (6m) lead (Qty 1 included)

## Dimensional Drawings



### Limited Warranty

ETI's two year limited warranty covering defects in workmanship and materials applies. Contact Customer Service for complete warranty information.

### Disclaimer

ETI makes no representations or warranties, either expressed or implied, with respect to the contents of this publication or the products that it describes, and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose. ETI reserves the right to revise this publication, and to make changes and improvements to the products described in this publication, without the obligation of ETI to notify any person or organization of such revisions, changes or improvements.

The ETI logo, Snow Switch, We Manage Heat, CIT, GIT, and SIT are registered trademarks of ETI. PD Pro and RCU are trademarks of ETI. Copyright © 2013 ETI. All rights reserved.

### Contacting Customer Service

For assistance, contact Customer Service. Office hours are from 8:00 AM until 5:00 PM ET.

**Email:** [info@networketi.com](mailto:info@networketi.com)

**Web:** [networketi.com](http://networketi.com)

**Mail:** ETI  
 1850 North Sheridan Street  
 South Bend, IN 46628